



Automated Shrink Packaging from product feeding , L-Sealing , auto belt transfer to Shrink Tunnel

Main Features

- Touch Screen Control for easy adjustment
- Teflon sprayed alloy Sealing knife life saving.
- Adjustable Sealing time and temperature depending on the thickness of plastic film.
- Adjustable conveyor and sealing height depending on product size.
- Large waste film collection spool less changeover
- Also available in Stainless Steel Version for Food Industries

Applications:

Foods Products, Trays, Boxes, Hardware, Cosmetics, Bottles, Bundling Applications

Specification :

Model	ALS-5500	DSH4000L
Max Packing size (mm)	$L+2H \leq 550, W+2H \leq 450, H \leq 140$	$W450 \times H200$
Min Packing Size (mm)	L: 60mm	
Max Sealing Size (mm)	$L550 \times W450$	
Power (Kw) / Voltage	(2.2Kw) 220V-50/60Hz	(11.7Kw) 380V 50/60Hz
Capacity	0-40pcs / min	0~10 m/min
Sealing Temperature	$180^{\circ}\text{C} - 250^{\circ}\text{C}$ depends on thickness of film and environment temperature	
Thickness of film (mu)	15 to 50	
Air pressure (Kg/cm ²)	5	
Packing Material	POF / PVC	
Machine Size (mm) / Weight (Kg)	$L1760 \times W940 \times H1580$ / 320kg	External $L1600 \times W900 \times H1400$ Tunnel ($L1500 \times W450 \times H200$) 250kg



UTOC (SINGAPORE) PTE LTD

BLOCK 2 , SKYTECH #08-19 , BUKIT BATOK ST 24 SINGAPORE 659480

TEL: (65) 6565 7477 FAX: (65) 6565 9454

EMAIL: office@utoc.sg WEBSITE: www.utoc.sg